


Declaration of Performance

DOP/ER/65/13

13N 65mm Stock Brick

Esker Readymix, Esker, Athenry, Co. Galway



- 1. Unique Identification code of the product type: Code 65/7.5- 13N 65mm Stock Brick
- 2. Intended use: Common masonry unit for use as external walls, or as internal walls, in load bearing or non-load bearing and civil engineering applications.
- 3. Manufacturer: Esker Readymix Ltd, Esker, Athenry Co. Galway.
- 4. Authorised Representative: N/A
- 5. System of AVCP: System 2+
- **6a. Harmonised Standard:** I.S. EN 771-3:2011 **Notified body:** NSAI:(No. 0050 CPR 0287)

7. Declared Performance

Characteristic	Declared Performance	Harmonised Technical Specification
Dimensions	(L x W x H) 215mm, 100mm, 65mm	I.S. EN 772-16
Dimensional Tolerances	Class D1	I.S. EN 772-16
Configuration	Category I, Group 1 unit	I.S EN 1996-1-1
Compressive Strength (Characteristic)	Category 1, 13N/mm ²	I.S. EN 772-1
Dimensional Stability	< 0.6mm/m	I.S. EN 772-14 / Table NA.7 EN 1996-1-1
Moisture Movement	< 0.0mmy m	1.3. LN 772-14 / Table NA.7 LN 1990-1-1
Bond Strength Shear Bond Strength	0.15N/mm²	I.S. EN 998-2 (Tabulated Value)
Flexural Bond Strength	0.5N/mm²	N/A
Reaction to Fire	Class A1	I.S. EN 1996-1-2 Annex A (Tabulated Value)
Water Absorption	≤20 g/m²s	N/A
Water Vapour Permeability	5/15µ	I.S. EN 1745 Annex A (Tabulated Value)
Direct airborne sound insulation: Gross Dry Density	>1900kg/m³	I.S. EN 772-13
Configuration	As above	N/A
Dimensions and tolerances	As above	N/A
Thermal Conductivity	0.90 - 1.00W/mK (λ10,dry Mat)	I.S. EN 1745 Annex A (Tabulated Value)
Durability Against Freeze Thaw	Suitable for use in: Masonry Condition Situations A1 and A2 as outlined in Table 14 of S.R. 325:2013+A2:2018 (Work below or near external ground level)-Mx2.1/2.2 • Net density ≥1500kg/m³ • Mean compressive strength ≥13N/mm² • Aggregate in accordance with I.S. EN12620 and S.R. 16:2016 • Mortar Strength Class: M4 for A1 or M6 for A2	I.S. EN 771-3
Dangerous Substances	NPD	See Note Below

8. N/A

https://www.eskerreadymix.ie/concrete-blocks/

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:







0050

Esker Readymix Esker, Athenry Co. Galway 17 0050 - CPR - 0287

EN 771-3

13N 65mm Solid Block

Category I - 215mm, 100mm, 65mm aggregate concrete masonry unit

(L x W x H) 215mm, 100mm, 65mm Dimensions Declared value

Dimensional Tolerences Declared Category Class D1

Group 1 unit to I.S. EN 1996-1-1 Configurtion Declared

Compressive Strength Characteristic 13N/mm²

Dimensional Stability

Moisture Movement Declared Value < 0.6mm/m

Bond Strength

Shear Bond Strength Declared value 0.15N/mm² (I.S. EN 998-2)(Tabulated Value)

Flexural Bond Strength Declared Value 0.5N/mm²


Reaction to Fire Declared Class A1 (I.S. EN 1996-1-2 Annex A)(Tabulated Value)

Water Absorption Declared Value ≤20 g/m²s

Water Vapour Permeability Declared value 5/15μ (I.S. EN 1745 Annex A)(Tabulated Value)

Direct airborne sound insulation:

Gross Dry Density Declared Configuration



Dimensions and tolerances Declared

Thermal Conductivity Declared Value 0.90 - 1.00 W/mK (λ10,dry Mat)(I.S. EN 1745 Annex A)(Tabulated Value)

Durability Against Freeze Thaw Declared

Suitable for use in:

Masonry Condition Situations A1 and A2 as outlined in

Table 14 of S.R. 325:2013+A2:2018

(Work below or near external ground level)-Mx2.1/2.2

• Net density ≥1500kg/m³

• Mean compressive strength
≥13N/mm²

NPD

- Aggregate in accordance with I.S. EN12620 and S.R.16:2016 Mortar Strength Class: M4 for A1 or M6 for A2

Dangerous Substances Declared